

APPLICATION GUIDE FOR Safety & Security Window Graphic Film

For the Safety & Security Window Graphic Film, compared to normal clear film, the biggest advantage is its function to reduce the damage when glass crush. Here below is Application guide on this material for your reference:

Ink compatibility: UV

Specification and suitability:

Size: 1.52m*30m/r, 50m/r, 100m/r, 200m/r, 300m/r

Thickness: 2 μ (suitable for glass thickness \square 5mm);

4 μ (suitable for glass thickness 5~10 mm);

8 μ (suitable for glass thickness \square 12 mm and windows on the roofs)

Durability: indoor 5 years, outdoor 3 years.

Application: Leave 3~4 days to let the ink adhesion to be best status

Due to its protective function, you could choose to apply inside when you would like to mainly protect inside people out of hurts when glass broken, and vice versa.

Before applying, should do pre clean on the glass, and make sure the operation circumstance be clean too.

Since the film is very thin, and if an improper adhering could be redone, before stick to the glass, you could spray some alkaline liquid to lubricate the glass surface. It'll make the film easy to tear off and re stick. After the whole project done, use a professional squeegee to make the left liquid out.

For test sample, pls. contact us at soyang@soyang.net
We also wait and welcome your visit at: www.soyang.net