

Scrimless Non-Curling Backlit Banner

PRODUCT: SoFlat- Backlit

FEATURES / APPLICATIONS:

- Super smooth surface makes it perfect for high resolution printing
- Scrimless banner material present super clear image
- Anti curl appearance at the edge
- Excellent printing performance
- Best suitable for high quality wide format light boxes

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC
STD Width	N/A	0.914/1.07/1.10/ 1.37/ 2.2/ 3.2m
STD Length	N/A	50m
Weight	DIN EN ISO 2286-2	440g/sq.m
Support Material	DIN 60001	PET
Coating	DIN 60001	PVC
Tensile Strength	DIN EN ISO 1421	1182 x1173N/5cm
Tear Strength	DIN 53363	34x27N/5cm
Temperature Resistance	N/A	- 20 ~ 70°C

INK PRINTABILITY

Solvent	Eco Solvent	UV
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Screen Printing	Dye Transfer	Dye Direct
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

NOTE: All above information shall only used as a guide; buyers shall independent products suitability. The mentioned data are average of test result and should not be used as a basis of lawsuit or warranty

Soyang Technologies Co., Ltd (Soyang Headquarters)

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918690

F. 0086-571-28918695

Soyang Haining Factory

No.36 Jinniu Road, Jianshan District, Haining City, Zhejiang PR, China.

Soyang Hangzhou Factory

No.1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

TECHNICAL DATA SHEET



IMPERIAL
36" /42" /43" /54" /87" /126"
55yd
13oz/sq.yd
Γ
⊙
133 x 132 lbs/inch
7.6x6.0lbs/inch
-4~158°F

Latex
Water based

ntly test and determine the
it be used for the purpose

Soyang Europe Ltd

Calder House Metcalf
Drive
Altham Industrial estate

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982