

Scrimless Non-Curling White/ Grey Frontlit Banner

PRODUCT: SoFlat- Frontlit

FEATURES / APPLICATIONS:

- Super smooth surface makes it perfect for high resolution printing
- Scrimless banner material
- Non curling appearance at the edge
- No lamination required
- Best suited for SOLO, pop-up, roll-up, X display, L display, screen scroll display, etc...

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
STD Width	N/A	0.914/ 1.37/ 2.2/ 3.2m	36" /54" /87" /126"
STD Length	N/A	50m	54.7yd
Weight	DIN EN ISO 2286-2	440g/sq.m	13oz/sq.yd
Support Cloth	DIN 60001	Polyester	
Coating	DIN 60001	PVC	
Tensile Strength	DIN EN ISO 1421	1182 x1173N/5cm	133 x 132 lbs/Inch
Tear Strength	DIN 53363	34x27N/5cm	7.6x6.0lbs/Inch
Temperature Resistance	N/A	-20~70°C	-4~158°F

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
☐	☐	☐	
Screen Printing	Dye Transfer	Dye Direct	Water based

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co., Ltd (Soyang Headquarters)

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China

www.soyang.net

P. 0086-571-28918697

F. 0086-571-28918695

Soyang Technical Textile (Zhejiang) Co., Ltd

No. 36 Jinniu Road, Jianshan District, Haining City, Zhejiang PR, China

Hangzhou Soyang Flexible Material Co., Ltd

No.1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House Metcalf Drive
Altham Industrial estate
Altham Lancashire BB5 5TU UK

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982