

# Prime Display UV



Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

## ST-117U

### BRIEF DESCRIPTION

- 100% polyester warp knitted fabric with a tight structure
- Max 5m width makes the product more widely used
- Specially developed for UV Printing

### FEATURES



PVC-FREE



PHTHALATE FREE



GOOD OPACITY



5m  
SUPER WIDE

### INK PRINTABILITY



UV



LATEX



SOL



ECO  
SOL

### MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	220 g/sq.m	6.5 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Weave Method	N/A	Warp-knitted	
Shielding Rate	ANSI PH2.19, ISO 5/2	60%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1 , EN13501-1	DIN 4102-1-B1, NFPA 701 Test1 , EN13501-1	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 500cm	197"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m/100m	55yds/110yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.

