

SD Acrylic Awning Fabric

PRODUCT: SD Acrylic

FEATURES

- Outstanding colorfastness
- Brilliant color brightness
- Long durability

APPLICATIONS

- Ideal for awning application.

SPECIFICATIONS	TEST METHOD	
Composition	100% Solution dye acrylic	
Weight	280gsm +/- 20gsm	DIN53352
	8.20oz +/- 0.6oz	ASTM D3776
Color	upon specific request	
Width	1200~2000mm	
Finish	Anti-stain, rot-proof, water-resistant	
Hydrostat	≥ 250mm	AATCC 127
Water repellency	≥95	AATCC 22
Tensile strength	1511N (Warp) 956N (Weft)	EN ISO 1421
Tear strength	64N (Warp) 50N (Weft)	ASTM D2261
UV Colorfastness	4	AATCC 16E, Option 3, 2000h

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co., Ltd
(Soyang Headquarter)

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918697
F. 0086-571-28918695

Soyang Haning Factory

No. 36 Jinniu Road, Jianshan District, Haining City, Zhejiang PR., China

Soyang Hangzhou Facotory

No. 1199, Gongyuan Xi Road, Fuyang, Hangzhou City, Zhejiang PR., China

Soyang Europe Ltd

Calder House Metcalf Drive, Altham Accrington, Lancashire BB5 5TU UK

www.soyang.co.uk

P. 0044-161 765 3400
F. 0044-1282 772 982