

SUPER CLEAR WINDOW GRAPHIC FILM

PRODUCT: ESCPET-115U

FEATURES / APPLICATIONS:

- 115micron clear PET film with adhesive in the back , smudge-free and PVC-free, 100% recyclable
- Low-tack, will not leave adverse effect on applying surface, no ghosting will be found even for long time use
- Very easy to cling onto glass, varnished wood, stainless steel, PVC, and other smooth surfaces
- Designed for UV printing with good image performace

MATERIAL DETAILS

PROPERTIES	TEST METHOD	RESULTS
Face Film		Transparent PET film
Face Film Thickness		115micron
Release Liner		50micron Matte BOPP
180°Peel strength (24Hr)		2.5g / 25mm
Apprearence		Clear
Service temperature		- 40°C ~ 100°C
Storage termpérature		10°C ~ 25°C
Storage humidity		30% ~ 60%
Shelf life		12 months
Dimensional Stability (300°F, 48Hr, applied to a		<0.1 inch
Chemical resistance		Resistant to most mild acids, alkalis, and salt solutions
Availavle Size		1.37x50m/roll

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
		<input type="checkbox"/>	
Screen Printing	Dye Transfer	Dye Direct	

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co., Ltd

(Soyang Headquarters)

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918690

F. 0086-571-28918695

Soyang Technical Textile (Zhejiang) Co.,Ltd

No.36 Jinniu Road,Jianshan District,Haining City, Zhejiang PR,China.

Hangzhou Soyang Flexible Materials Co., Ltd

No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House Metcalf Drive
Altham Industrial estate
Altham Lancashire BB5 5TU UK

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982