

Flashing Static Film

PRODUCT: PSF-180F

FEATURES & APPLICATIONS

- 180micron transparent frosted PVC film with 40micron PET liner, non-adhesive
- Mostly used for glass, lenses, high-gloss plastic surfaces, and acrylic and other smooth surfaces
- It has obvious effects on product surface production, enhancing product value
- Compatible with Sol/Eco-sol/UV/Latex inks

MATERIAL DETAILS

PROPERTIES	TEST METHOD	RESULTS
Face Film		
Material		Monomer PVC film
Color		Transparent, Frosted
Thickness	GB/T6672	180 micron
Weight	ISO 4591	230 gsm
Release Liner		
Material		PET liner
Thickness	GB/T6672	40 micron
Other		
180°Peel Strength	Steel, 20min	0.368 N/inch
Storage Temperature		20°C ~ 25°C
Storage Humidity		50% ~ 55%
Shelf Life		12 months
Width Available		0.914/1.07/1.27/1.52m
Regular Length		50m

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Screen Printing	Dye-sub Transfer	Dye-sub Direct	Water based

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co., Ltd (Soyang Headquarter)

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918685

F. 0086-571-28918695

Soyang Technical Textile (Zhejiang) Co., Ltd

No.36 Jinniu Road, Jianshan District, Haining City, Zhejiang PR, China.

Hangzhou Soyang Flexible Materials Co., Ltd

No.1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House Metcalf Drive Altham Industrial estate Altham Lancashire BB5 5TU UK

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982