

# Solar Blockout Pro



## SL-BL03

Soyang's innovative eco range: PVC-Free. Low-emission.  
Oekotex Standard 100 Certificated.

### BRIEF DESCRIPTION

- 100% PVC free, tight structure, smooth hand feel
- W/B/W structure makes it full opacity
- Anti-curling, excellent consistency on both sides
- Can be used as indoor hanging banner, roll up, display, curtain or short time outdoor pole banner, etc

### FEATURES



PVC-FREE



PHthalate FREE



FULL OPACITY



FIRE-RESISTANT

### INK PRINTABILITY



### MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	350 g/sq.m	10.3 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100% Polyester	
Yarn Dtex	DIN EN ISO 2060, ASTM D 1907	330X330 dtex	300x300 denier
Yarn Density	ASTM D3775	30x17	
Shielding Rate	ANSI PH2.19, ISO 5/2	100%	
Tensile Strength	DIN EN ISO 1421	1900x1090 N/5cm	217x125 lbs/inch
Tear Strength	DIN 53363	160 x70 N	36x16 lbs
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds
Storage Temperature		10 ~40°C	39~89°F
Storage Humidity		10~70%RH	
Shelf Life		12 months at recommended storage temperature and humidity	

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.