

13oz/440gsm Cost-effective Frontlit



Soyang's PVC banner&mesh range. Supported by full industry chain. Compatible with various printing methods.

B01-440(3050)

BRIEF DESCRIPTION

- Great cost-effective for frontlit display
- Smooth surface, matte & gloss are available
- For short-time indoor& outdoor banners, signs & displays

FEATURES



INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	440g/sq.m	13oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060 ASTM D1907	330x550 dtex	300x500 denier
Tensile Strength	DIN EN ISO 1421	683x560N/5cm	79x63 lbs/inch
Tear Strength	DIN 53363	112x100 N	25x24 lbs
Adhesion	DIN 53357	No delamination	
Flame Resistance	DIN 4102-1-B1, NFPA 701, M2	DIN 4102-1-B1, NFPA 701, M2	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.

