

780gsm Heavy Duty Blockout

Soyang's PVC banner&mesh range. Supported by full industry chain. Compatible with various printing methods.

BLOW-780

BRIEF DESCRIPTION

- Super high tenacity blockout with matte and delicate surface
- The heaviest and also most durable blockout banner, perfect opacity
- Best suited for outdoors under harsh conditions when banner opacity and two sides printing is required

FEATURES



INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	780g/sq.m	23oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060 ASTM D1907	1100x1100 dtex	1000x1000 denier
Tensile Strength	DIN EN ISO 1421	2300x2450 N/5cm	263x280 lbs/inch
Tear Strength	DIN 53363	583x430 N	120x97 lbs
Adhesion	DIN 53357	No delamination	
Flame Resistance	DIN 4102-1-B1, NFPA 701, M2	DIN 4102-1-B1, NFPA 701, M2	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 500cm	197"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.