

Super Tenacity Blockout 610



Soyang's PVC banner&mesh range. Supported by full industry chain. Compatible with various printing methods.

BLOW-610 (5028)

BRIEF DESCRIPTION

- 500DX500D, 28X28 base fabric with woven structure makes it more stable & durable
- Smooth surface, available to print on both sides with high resolution and consistent quality
- Best suited for indoor and outdoor advertising applications

FEATURES



INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	610g/sq.m	18oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060 ASTM D1907	550x550 dtex	500x500 denier
Tensile Strength	DIN EN ISO 1421	2222x2215N/5cm	254x253 lbs/inch
Tear Strength	DIN 53363	372x362 N	84x82 lbs
Adhesion	DIN 53357	No delamination	
Flame Resistance	DIN 4102-1-B1, NFPA 701, M2	DIN 4102-1-B1, NFPA 701, M2	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.

