

# High Tenacity Premium Blockout 610



Soyang's PVC banner&mesh range. Supported by full industry chain. Compatible with various printing methods.

## BLOW-610(1018)

### BRIEF DESCRIPTION

- 1000DX1000D, 18X18 base fabric with woven structure makes it more stable & durable
- Super smooth surface on both sides for high resolution printing
- Perfect opacity makes it printable on both sides with consistent quality
- Best suited for outdoor applications

### FEATURES



### INK PRINTABILITY



### MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	610g/sq.m	18oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060 ASTM D1907	1100x1100 dtex	1000x1000 denier
Tensile Strength	DIN EN ISO 1421	1910x1700 N/5cm	218x194 lbs/inch
Tear Strength	DIN 53363	240x250 N	54x56 lbs
Adhesion	DIN 53357	No delamination	
Flame Resistance	DIN 4102-1-B1, NFPA 701, M2	DIN 4102-1-B1, NFPA 701, M2	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.

