

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

Dieulight Pro

ST-6091

BRIEF DESCRIPTION

- 100% polyester woven coated fabric with smooth surface, light weight
- Very good light transmittance, with no light leakage on light box
- Brilliant printing output for solvent and latex inks with good ink fastness
- Mainly used as backlit, frame fabric, also available as ceiling deco, banner, flag, etc

FEATURES









INK PRINTABILITY









MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	140 g/sq.m	4.1 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	
Weave Method	N/A	Woven	
Light Transmittance	ANSI PH2.19, ISO 5/2	(50±5)%	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.







