

550gsm Standard Blockout Banner



Soyang's PVC banner&mesh range. Supported by full industry chain. Compatible with various printing methods.

BLO-550(5050)

BRIEF DESCRIPTION

- Best value blockout banner with matte and delicate surface
- Printable on both sides with uniform printing quality
- Good opacity, suited for indoor applications or outdoor under low stress conditions

FEATURES



INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	550g/sq.m	16oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Yarn Dtex	DIN EN ISO 2060 ASTM D1907	550x550 dtex	500x500 denier
Tensile Strength	DIN EN ISO 1421	950x700 N/5cm	106x78 lbs/inch
Tear Strength	DIN 53363	165x120 N	37x27 lbs
Adhesion	DIN 53357	No delamination	
Flame Resistance	DIN 4102-1-B1, NFPA 701, M2	DIN 4102-1-B1, NFPA 701, M2	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.

