

Polarlight

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

ST-603U

BRIEF DESCRIPTION

- 100% polyester woven coated fabric with super smooth surface
- Soft hand feel, good light transmittance when rear-illuminated
- Perfect as LED light box, frame system material

FEATURES



PVC-FREE



PHTHALATE FREE



GOOD TRANSMITTANCE



SOFT HANDFEEL

INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	140 g/sq.m	4.1 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Weave Method	N/A	Woven	
Light Transmittance	ANSI PH2.19, ISO 5/2	(34±5)%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.