Nightview Backdrops Memphis Plus ST-2104T/ST-2104D



Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

BRIEF DESCRIPTION

- 100% warp-knitted polyester fabric with enhanced white surface
- Uncoated greyback offers very perfect opacity, ideal as backdrops
- Soft hand touch, light stretch & truly crease free, easy for transportation and installation
- Highly recommended to be used as frame, light curl geometric, grandformat, etc

FEATURES



INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	330 g/sq.m	9.7 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%Polyester	
Weave Method	N/A	Warp-knitted	
Shrinkage	ISO 9866-2-1991	≤2%	
Shielding Rate	ANSI PH2.19, ISO 5/2	99%	
Elasticity	Length*Width=200*50mm, Speed=100mm/min, Tension=20N	Warp: 10%	Weft: 5%
Flame Resistance	EN13501-1, DIN 4102-1-B1, NFPA 701	EN13501-1,DIN 4102-1-B1, NFPA 701	
Recommend Fixation Temperature	N/A	190°C-200°C, 30s-50s	
Width Available	DIN EN ISO 3759, ASTMD751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTMD751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.

CON

IN TEXTILES

STANDARD 100

20.HCN.12564 HOHENSTEIN HTTI





