

## StarLight Standard

### ST-600U

#### BRIEF DESCRIPTION

- 100% polyester woven coated fabric
- Really tight structure, with no light leakage when used as backlit fabric
- Perfect with UV inks, also workable with Sol, Eco-sol, Latex

#### FEATURES



PVC-FREE



PHthalate FREE



GOOD TRANSMITTANCE



TIGHT STRUCTURE

#### INK PRINTABILITY



#### MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	160g/sq.m	4.7 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Weave Method	N/A	Woven	
Light Transmittance	ANSI PH2.19, ISO 5/2	47%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.