

White Cloud Blockout Elite

ST-2331T/D

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

BRIEF DESCRIPTION

- 100% polyester woven fabric with W/B/W structure
- Offers enhanced whiteness and a soft hand feel for superior comfort
- Optimal opacity ensures high-quality double side printing effect
- Ideal for using as indoor hanging banner, pole-banner, roll-up, blockout display, curtain, etc

FEATURES



INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	320 g/sq.m	9.4 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%polyester	
Weave Method	N/A	Woven	
Shrinkage	ISO 9866-2-1991	≤2%	
Shielding Rate	ANSI PH2.19, ISO 5/2	95%	
Tensile Strength	DIN EN ISO 1421	1276x2408 N/5cm	146x275 lbs/inch
Tear Strength	DIN53363	437x489 N	98x110 lbs
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1	
Recommend Fixation Temperature	N/A	190°C-200°C, 30s-50s	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall be independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.