

## Premium Coated Tent Fabric 19oz/650gsm

Soyang's industrial technical textiles series offers tailored solutions with the broadest range and top-tier quality.

**TFK112020**

### BRIEF DESCRIPTION

- High tensile, tear and adhesion strength
- Good resilience
- Ideal for high-ends projects, mega marquees, or mobile constructions at harsh conditions

### FEATURES



### MATERIAL DETAILS

SPECIFICATIONS	TEST METHOD	RESULTS
Composition	DIN 53830    DIN60001	1100 x 1100 Dtex    8 x 8/cm
	ASTM D 751	1000D x 1000D    20 x 20/inch
Weight	DIN53352	650gsm ± 20gsm
	ASTM D 751	19oz
Lacquering		1/1 Acrylic (Upon request)
Surface Finish		Glossy
Color		White
Breaking Strength (Warp x Weft )	DIN 53354	2500 x 2200 N/5cm
	FS 5100	568 x 500 lbs/2"
Tearing Strength (Warp x Weft )	DIN 53363	300 x 250 N
	FS 5100	68 x 56 lbs
Adhesion Strength	DIN 53357	100N/5cm
	FS 5970	22 lbs/2"
Width		1000 - 3200mm
		36" - 126"
Fire Resistance		B1, B2, NFPA 701
Temperature Resistance	DIN 53372	-30°C - 70°C
	FS 5874	-20°F - 158°F

NOTE: All characteristics could be customized upon request, such as fire retardant, higher color fastness etc. All above information shall only be used as a guide; buyers shall independently test and determine the products' suitability. The mentioned data are the average of the test results and should not be used for the purpose of a lawsuit or warranty.