

Metallic Silver Coated Tent Fabric TFK112323BS

Soyang's industrial technical textiles series offers tailored solutions with the broadest range and top-tier quality.

BRIEF DESCRIPTION

- The silver lacquering makes the temporary fabric structures a metallic look, and gives a feeling more permanent and solid of the structures
- The silver lacquering makes the dirt less visible, and reduces the costs on washing
- Silver/White plus black layer version with superior opacity
- -Ideal for fabric structures

FEATURES









MATERIAL DETAILS

| | DIN 53830 DIN60001 | |
|------------------------|--------------------|---|
| Composition | | 1100 x 1100 Dtex 9 x 9/cm blockout |
| Composition | ASTM D 751 | 1000D x 1000D 23 x 23/inch blockout |
| Weight | DIN53352 | 850gsm ± 20gsm |
| weight | ASTM D 751 | 25oz |
| Lacquering | | Silver Acrylic lacquering/ Clear Acrylic lacquering |
| Surface Finish | | Glossy |
| Color | | Silver/White |
| Breaking Strength | DIN 53354 | 2800 x 2500 N/5cm |
| (Warp x Weft) | FS 5100 | 640 x 570 lbs/2" |
| Tearing Strength | DIN 53363 | 450 x 350 N |
| (Warp x Weft) | FS 5100 | 103 x 80 lbs |
| Adhesion Strength | DIN 53357 | 100N/5cm |
| Adilesion strength | FS 5970 | 22.5 lbs/2" |
| Width | | 1000 - 3200mm |
| Width | | 36" - 126" |
| Fire Resistance | | B1, B2, NFPA 701 |
| Temperature Resistance | DIN 53372 | -30°C - 70°C |
| remperature nesistance | FS 5874 | - 20 °F - 158 °F |

NOTE: All characteristics could be customized upon request, such as fire retardant, higher color fastness etc. All above information shall only be used as a guide; buyers shall independently test and determine the products' suitability. The mentioned data are the average of the test results and should not be used for the purpose of a lawsuit or warranty.