

Premium Coated Tent Fabric 22oz/750gsm

Soyang's industrial technical textiles series offers tailored solutions with the broadest range and top-tier quality.

TFK112323B 750

BRIEF DESCRIPTION

- High tensile, tear and adhesion strength
- Good resilience
- Ideal for high-ends projects, mega marquees, or mobile constructions at harsh conditions

FEATURES



UV RESISTANT



ABRASION-RESISTANT



FIRE-RESISTANT



MILDEW RESISTANT



SELF-CLEANING

MATERIAL DETAILS

SPECIFICATIONS	TEST METHOD	RESULTS
Composition	DIN 53830 DIN60001	1100 x 1100 Dtex 9 x 9/cm blackout
	ASTM D 751	1000D x 1000D 23 x 23/inch blackout
Weight	DIN53352	750gsm ± 20gsm
	ASTM D 751	22oz
Lacquering		1/1 Acrylic (Upon request)
Surface Finish		Glossy
Color		White
Breaking Strength (Warp x Weft)	DIN 53354	2800 x 2500 N/5cm
	FS 5100	636 x 568 lbs/2"
Tearing Strength (Warp x Weft)	DIN 53363	400 x 350 N
	FS 5100	90 x 79 lbs
Adhesion Strength	DIN 53357	100N/5cm
	FS 5970	22 lbs/2"
Width		1000 - 3200mm
		36" - 126"
Fire Resistance		B1, B2, NFPA 701
Temperature Resistance	DIN 53372	-30℃ - 70℃
	FS 5874	-20°F - 158°F

NOTE: All characteristics could be customized upon request, such as fire retardant, higher color fastness etc. All above information shall only be used as a guide; buyers shall independently test and determine the products' suitability. The mentioned data are the average of the test results and should not be used for the purpose of a lawsuit or warranty.