

Solar Blockout Elite

SL-BL04



Soyang's innovative Eco range: PVC-Free. Low-emission.

Oekotex Standard 100 Certificated.

BRIEF DESCRIPTION

- 100% PVC free woven coated fabric, very tight structure
- W/B/W structure makes it full opacity, excellent two-sided consistency
- Very good strength, stiff & smooth, anti-curling
- Can be widely used as roll up, roller blind, blockout banner, hanging banner, display, etc

FEATURES



PVC-FREE



PHTHALATE FREE



TIGHT STRUCTURE



FULL OPACITY



FIRE-RESISTANT

INK PRINTABILITY



UV



LATEX



SOL



ECO SOL

MATERIAL DETAILS

| PROPERTIES | TEST METHOD | METRIC | IMPERIAL |
|------------------|---|--|------------------|
| Total Weight | DIN EN ISO 2286-2, ASTM D751 | 340 g/sq.m | 10 oz/sq.yd |
| Base Fabric | DIN 60001, ASTM D7641 | 100% Polyester | |
| Weave Method | N/A | Woven | |
| Yarn Dtex | DIN EN ISO 2060, ASTM D 1907 | 330X660 dtex | 300x600 denier |
| Shielding Rate | ANSI PH2.19, ISO 5/2 | 100% | |
| Tensile Strength | DIN EN ISO 1421 | 1880x1770 N/5cm | 215x202 lbs/inch |
| Tear Strength | DIN 53363 | 188 x162 N | 42x36 lbs |
| Flame Resistance | EN13501-1, DIN 4102-1-B1, NFPA 701 Test1 | EN13501-1, DIN 4102-1-B1, NFPA 701 Test1 | |
| Width Available | DIN EN ISO 3759, ASTM D751-2006 | Max 320cm | 126" |
| Standard Length | DIN EN ISO 3759, ASTM D751-2006 | 50m | 55yds |
| Storage Humidity | | 10~70%RH | |
| Shelf Life | | 12 months at recommended storage temperature and humidity | |

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.