

Best-value Laminated Tent Fabric 15oz/510gsm

TFL5599

Soyang's industrial technical textiles series offers tailored solutions with the broadest range and top-tier quality.

BRIEF DESCRIPTION

- Good tensile and tear strength
- Good stretch ability and softness
- Ideal for general mobile constructions aiming for medium-term applications

FEATURES



UV RESISTANT



ABRASION-RESISTANT



FIRE-RESISTANT



MILDEW RESISTANT



SELF-CLEANING

MATERIAL DETAILS

SPECIFICATIONS	TEST METHOD	RESULTS
Composition	DIN 53830 DIN60001	550 x 550 Dtex 3.5 x 3.5/cm
	ASTM D 751	500D x 500D 9 x 9/inch
Weight	DIN53352	510gsm ± 20gsm
	ASTM D 751	15.8oz
Lacquering		1/1 Acrylic (Upon request)
Surface Finish		Glossy
Color		White
Breaking Strength (Warp x Weft)	DIN 53354	872 x 662 N/5cm
	FS 5100	198 x 150 lbs/2"
Tearing Strength (Warp x Weft)	DIN 53363	163 x 149 N
	FS 5100	37 x 33 lbs
Width		1000 - 3200mm
		36" - 126"
Fire Resistance		B1, B2, NFPA 701
Temperature Resistance	DIN 53372	-30℃ - 70℃
	FS 5874	-20°F - 158°F

NOTE: All characteristics could be customized upon request, such as fire retardant, higher color fastness etc. All above information shall only be used as a guide; buyers shall independently test and determine the products' suitability. The mentioned data are the average of the test results and should not be used for the purpose of a lawsuit or warranty.