

16 OZ Dual Mirror-faced PVC Blockout Tarp

TFL1199BDG

Soyang's industrial technical textiles series offers tailored solutions with the broadest range and top-tier quality.

BRIEF DESCRIPTION

- Gloss finish on both sides allows its high ability of anti-dirt, saving your costs on cleaning and keeps your events more glamorous
- Strong enough structure suitable for temporary space application
- Definitely best value for meeting your budget

APPLICATIONS

- Short-term mobile fabric structures for party, outdoor assemble, or any temporary activities

MATERIAL DETAILS

SPECIFICATIONS	TEST METHOD	RESULTS
Composition	DIN 53830 DIN60001	1100 x 1100 Dtex 3.5 x 3.5/cm
	ASTM D 751	1000D x 1000D 20 x 20/inch
Weight	DIN53352	540gsm ± 20gsm
	ASTM D 751	16oz
Surface Finish		Glossy
Color		White
Breaking Strength (Warp x Weft)	DIN 53354	1327 x 1772 N/5cm
	FS 5100	301 x 402 lbs/2"
Tearing Strength (Warp x Weft)	DIN 53363	336 x 348 N
	FS 5100	76 x 79 lbs
Adhesion Strength	DIN 53357	29.5 N/5cm
	FS 5970	6.7 lbs/2"
Width		1000 - 3200mm
		36" - 126"
Fire Resistance		B1, B2, NFPA 701
Temperature Resistance	DIN 53372	-30°C - 70°C
	FS 5874	-20°F - 158°F

NOTE: All characteristics could be customized upon request, such as fire retardant, higher color fastness etc. All above information shall only be used as a guide; buyers shall independently test and determine the products' suitability. The mentioned data are the average of the test results and should not be used for the purpose of a lawsuit or warranty.