



TECHNICAL DATA SHEET



Dura Floor

PRODUCT: DGF-001

Features:

- Matte finish with an anti-slip design for safety in high-traffic areas
- Cushioned PVC foam backing for enhanced comfort underfoot
- High printing stability for vibrant colors with UV and Latex inks
- Easy to cut with clean edges, minimizing material waste
- Designed for indoor promotional spaces, exhibition halls & retail zones

MATERIAL DETAILS

PROPERTIES	TEST METHOD	TEST RESULT
Surface		Polyester
Backing		PVC
Weight	ASTM D751	950gsm
Thickness		1.9mm
Tear Strength	DIN 53363	164x117 N/5cm
Tensile Strength	EN ISO 1421	2211x1479 N/5cm
Flame Resistance	DIN 4102-1-B1, NFPA 701	DIN 4102-1-B1, NFPA 701
Available Size		Up to 3.2m/126"

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
		<input type="checkbox"/>	<input type="checkbox"/>
Screen Printing	Dye-sub Transfer	Dye-sub Direct	Water based

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co., Ltd (Soyang Headquarter)

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918690

F. 0086-571-28918695

Soyang Technical Textile (Zhejiang) Co.,Ltd

No.36 Jinniu Road,Jianshan District,Haining City, Zhejiang PR,China.

Hangzhou Soyang Flexible Material Co., Ltd

No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House Metcalf
DriveAltham Industrial
estateAltham Lancashire BB5 5TU
UK

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982