

Prime Textile Wall Covering

ST-703T/ST-703D

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

BRIEF DESCRIPTION

- New warp-knitted textile wall covering with grey rough back which has great flatness;
- With excellent opacity, can be used on the wall with any background color, even some defect walls;
- Always used in conjunction with glue, easy to operate;
- Also can be used as roll-up display, frame, art decoration, etc;
- Compatible with dye-sub paper transfer or dye-sub direct printing with vivid colors.

FEATURES



INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	320 g/sq.m	9.4 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	Polyester	Polyester
Weave Method	N/A	Warp-knitted 3 bar	
Shrinkage	ISO 9866-2-1991	≤3%	
Shielding Rate	ANSI PH2.19, ISO 5/2	98%	
Flame Resistance	EN13501-1, DIN 4102-1-B1	EN13501-1, DIN 4102-1-B1	
Recommend Fixation Temperature	N/A	190°C-200°C, 30s-50s	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 500cm	197"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.