# **Nightstar Blackback Plus**



ST-216P

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

## **BRIEF DESCRIPTION**

- 100% warp-knitted polyester fabric, white surface & black back offers full opacity
- Width up to 5M, excellent for UV, Latex and dye-sub printing with good resolution
- Widely be used as backdrops, Pop-up, frame, exhibition, etc

## **FEATURES**









## **INK PRINTABILITY**









## **MATERIAL DETAILS**

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	260 g/sq.m	7.6oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%polyester	
Weave Method	N/A	Warp-knitted	
Shrinkage	ISO 9866-2-1991	≤3%	
Shielding Rate	ANSI PH2.19, ISO 5/2	100%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	
Recommend Fixation Temperature	N/A	190°C, 30s	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Up to 500cm	Up to 197"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds
NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above			

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.







