

## Coated Tarpaulin 18oz/610gsm

### IDFK112020

Soyang's industrial technical textiles series offers tailored solutions with the broadest range and top-tier quality.

#### BRIEF DESCRIPTION

- High tensile and tear strength, and good welding ability
- A variety of options on colors
- Ideal for truck covers, container covers, temporary cargo covers, etc

#### FEATURES



#### MATERIAL DETAILS

SPECIFICATIONS	TEST METHOD	RESULTS
Composition	DIN 53830 DIN60001	1100 x 1100 Dtex 8 x 8/cm
	ASTM D 751	1000D x 1000D 20 x 20/inch
Weight	DIN53352	610gsm
	ASTM D 751	18oz
Lacquering		1/1 Acrilic (upon request)
Surface Finish		Glossy or matte
Color		Normal Color
Breaking Strength (Warp x Weft )	DIN 53354	2500 x 2300 N/5cm
	FS 5100	570 x 530 lbs/2"
Tearing Strength (Warp x Weft )	DIN 53363	350 x 330 N
	FS 5100	80 x 75 lbs
Adhesion Strength	DIN 53357	100 N/5cm
	FS 5970	22.5 lbs/2"
Width		1000 - 3200mm
		36" - 126"
Fire Resistance		B1, B2, NFPA 701
Temperature Resistance	DIN 53372	-30°C - 70°C
	FS 5874	-20°F - 158°F

NOTE: All characteristics could be customized upon request, such as fire retardant, higher color fastness etc. All above information shall only be used as a guide; buyers shall independently test and determine the products' suitability. The mentioned data are the average of the test results and should not be used for the purpose of a lawsuit or warranty.