

Soflat Blockout

PRODUCT: Soflat Blockout
Features & Applications:

- Scrimless Non-Curling Banner
- Super Smooth Surface
- Excellent Printing Performance
- Ideal for hanging graphics, exhibition, retail display and so on

MATERIAL DETAILS

PROPERTIES	TEST METHOD	RESULTS
Raw Material		PET
Total Weight		510g/sq.m 15oz/sq.yd
Surface		White
Back		White
Width Available		Up to 3.2m/126"
Regular length		50m

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
☐	☐	☐	☐
Screen Printing	Dye-sub Transfer	Dye-sub Direct	Water based

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co., Ltd
(Soyang Headquarter)

West 19th FL, Yongtong Information plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR., China.

www.soyang.net

P. 0086-571-28918685

F. 0086-571-28918695

Soyang Technical Textile (zhejiang) Co.,Ltd

No.36 Jinniu Road,Jianshan District,Haining City, Zhejiang PR,China.

Hangzhou Soyang Flexible Material Co.,Ltd

No,1199 Gongyuan Xi Rd, Fuyang, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House Metcalf DriveAltham
Industrial estateAltham Lancashire
BB5 5TU UK

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982