

Starlight Dura Superior

ST-6011S



Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

BRIEF DESCRIPTION

- 100% polyester woven coated fabric featuring a dense structure and enhanced white finish
- Superior softness with excellent anti-wrinkle performance
- Exceptional light transmittance--bright and uniform illumination, ideal for high-end backlit applications
- High printing stability delivering brilliant, vivid colors with outstanding ink fastness
- Also can widely used in frame systems, tents, sun-umbrellas, etc

FEATURES



INK PRINTABILITY



MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	190 g/sq.m	5.6 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%polyester	
Weave Method	N/A	Woven	
Shrinkage	210°C, 30s	≤3%	
Light Transmittance	ANSI PH2.19, ISO 5/2	(45±5)%	
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	DIN 4102-1-B1, NFPA 701 Test1, EN13501-1	
Recommend Fixation Temperature	N/A	190°C-200°C, 30s-50s	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 500cm	197"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.