

Nightstar Blackback Basic

ST-226T/ST-226D

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

BRIEF DESCRIPTION

- 100% warp-knitted polyester fabric with W/B structure
- Full opacity, widely used as frame, backdrops, pop-up, etc
- Light weight, convenient for transportation and installation

FEATURES



PVC-FREE



PHthalate FREE



FULL OPACITY



FIRE-RESISTANT



5m
SUPER WIDE

INK PRINTABILITY



DYE direct



DYE paper



UV



LATEX

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	250 g/sq.m	7.4 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100% polyester	
Weave Method	N/A	Warp-knitted	
Shrinkage	ISO 9866-2-1991	≤3%	
Shielding Rate	ANSI PH2.19, ISO 5/2	100%	
Flame Resistance	EN13501-1, DIN 4102-1-B1, NFPA 701 Test1	EN13501-1, DIN 4102-1-B1, NFPA 701 Test1	
Recommend Fixation Temperature	N/A	190°C-200°C, 30s-50s	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 500cm	197"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.