

Sarga Deco Fabric

EXT-161

EXPLORE™

Product series with good quality & competitive price, high cost performance

BRIEF DESCRIPTION

- 100% polyester woven fabric with twill structure
- Smooth and soft handfeel and excellent drape, truly wrinkle free
- Wide-range in application, popularly used as table covering, frame, display, etc

FEATURES



PVC-FREE



PHTHALATE FREE



WRINKLE-RESISTANT



HIGH TENACITY

INK PRINTABILITY



DYE paper



DYE direct

MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	200g/sq.m	5.9 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%polyester	
Weave Method	N/A	Woven	
Shrinkage	210°C, 30s	≤2%	
Shielding Rate	ANSI PH2.19, ISO 5/2	(60±3)%	
Tensile Strength	DIN EN ISO 1421	1566x1028N/5cm	178x117 lbs/inch
Tear Strength	DIN53363	290x240 N	65x54 lbs
Recommend Fixation Temperature	PD-3200RXD-260	190~200°C, 30~50s	
Width Available	DIN EN ISO 3759, ASTM D751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTM D751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.