

# Nightview Greyback Nyx

## ST-2105T/ST-2105D

Soyang's comprehensive range: PVC-Free. Supported by full industry chain. Compatible with various printing methods.

### BRIEF DESCRIPTION

- 100% polyester tight-knit textile with a flawlessly smooth finish
- Unrivaled brilliant whiteness with a luxurious texture and ultra-soft touch
- Uncoated for eco-conscious excellence, with a grey back providing exceptional opacity
- Offers optimal elasticity and is truly wrinkle-free, ensuring ease of handling and transportation
- Ideal for luxurious displays, high-end SEG frames, 3D geometric designs, hanging graphics, etc

### FEATURES



### INK PRINTABILITY



### MATERIAL DETAILS

PROPERTIES	TEST METHOD	METRIC	IMPERIAL
Total Weight	DIN EN ISO 2286-2, ASTM D751	320 g/sq.m	9.4 oz/sq.yd
Base Fabric	DIN 60001, ASTM D7641	100%Polyester	
Weave Method	N/A	Warp-knitted	
Shrinkage	ISO 9866-2-1991	≤2%	
Shielding Rate	ANSI PH2.19, ISO 5/2	99%	
Elasticity	Length*Width=200*50mm, Speed=100mm/min, Tension=20N	Warp: 5% Weft: 5%	
Flame Resistance	EN13501-1, DIN 4102-1-B1, NFPA 701	EN13501-1, DIN 4102-1-B1, NFPA 701	
Recommend Fixation Temperature	N/A	190°C-200°C, 30s-50s	
Width Available	DIN EN ISO 3759, ASTMD751-2006	Max 320cm	126"
Standard Length	DIN EN ISO 3759, ASTMD751-2006	50m	55yds

NOTE: It is normal that the weight of most products will have an average fluctuation of 5%. All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty.