

PP Floor Graphic Sticker

PRODUCT: FG-1825PP

Features& Applications:

- Translucent & PVC-free PP film
- Anti-slip & abrasion-resistant
- Ideal for floor graphics, indoor advertising, and decorative applications

MATERIAL DETAILS

PROPERTIES	TEST METHOD	RESULTS
Film Material	GB/T6672-2001	180±10micron translucent PP film(R12 grade)
Adhesive Type		Solvent-based permanent acrylic pressure-sensitive adhesive, transparent
Coating Weight(Dry)		27±2gsm
Release Liner	GB/T6672-2001	25±5micron PET
Dimensional Stability	FINAT-14	Max. 0.8mm
Adhesion (Initial)	FINAT FTM-1, stainless steel	≥8N/25mm
Adhesion (Ultimate)	FINAT FTM-1, stainless steel	≥10N/25mm
Release	FINAT-4	5-25gf/25mm
Shelf Life	Stored at 24°C/50-60% RH	12months
Durability (Unprinted)	Vertical exposure	12months
Available Width		1.07/1.27/1.37/1.52M

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
		☐	
Screen Printing	Dye-sub Transfer	Dye-sub Direct	Water based

NOTE: All above information shall only be used as a guide; buyers shall independently test and determine the product's suitability. The mentioned data are average of test results and should not be used for the purpose of lawsuits or warranty claims.

**Soyang Technologies Co., Ltd
(Soyang Headquarter)**

West 19th FL, Yongtong Information Plaza, No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR, China.

www.soyang.net

P. 0086-571-28918690

F. 0086-571-28918695

Soyang Technical Textile (Zhejiang) Co., Ltd

No.36 Jinniu Road, Jianshan District, Haining City, Zhejiang PR, China.

Hangzhou Soyang Flexible Material Co., Ltd

No.1268, Gongwang Street, Fuyang District, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House Metcalf Drive Altham Industrial Estate Altham Lancashire BB5 5TU UK

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982