TECHNICAL DATA SHEET

Floor Graphic Sticker

PRODUCT: FG-1712

Features& Applications:

- Good slip resistance for floor graphic applications
- Suitable for protecting floor graphics on smooth and semi-smooth surfaces

MATERIAL DETAILS

PROPERTIES	TEST METHOD	RESULTS
Film Material	GB/T6672	170micron transparent frosted monomeric PVC Film
Film Weight	IS04591	200±10gsm
Adhesive type	IS04591	35±2gsm transparent permanent acrylic pressure-sensitive adhesive
Release Liner	IS04591	120gsm single-side PE-coated white release paper with grey grid
Initial Tack	Initial Tack Tester	≥ No. 10 steel ball
180° Peel Adhesion (20 min)	Tensile Testing Machine	≥ 7 N/in
Holding Power (min)	Holding Power Tester	≥ 3000
Shelf Life		12 months (22 ± 3°C, 50–55% RH)
Available Width		0.914/1.07/1.27/1.37/1.52m
Regular Length		50m

INK PRINTABILITY

Solvent	Eco Solvent	UV	Latex
Screen Printing	**Dye-sub Transfer**	**Dye-sub Direct**	**Water based**

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty

Soyang Technologies Co., Ltd (Soyang Headquarter)

West 19th FL, Yongtong Information Plaza,
No. 141 Huancheng Bei Road, Hangzhou City, Zhejiang PR, China

www.soyang.net

P. 0086-571-28918690

F. 0086-571-28918695

Soyang Technical Textile (Zhejiang) Co., Ltd

No.36 Jinniu Road, Jianshan District,Haining City, Zhejiang PR, China.

Hangzhou Soyang Flexible Material Co., Ltd

No.1268, Gongwang Street, Fuyang District, Hangzhou City, Zhejiang, PR, China

Soyang Europe Ltd

Calder House, Metcalf Drive, Altham, Accrington, BB5 5TU, UK

www.soyang.co.uk

P. 0044 (0) 161 765 3400

F. 0044 (0) 1282 772982